



460

4802-200

4805

3 1/8" LINE 50 ohms nominal

specifications Accuracy: ±5% of full scale Insertion VSWR: 1.05 max.

Model No.	Frequ. Range MHz	Power Range kW	Flg/Unflg	No. of Sockets	Scale Divisions	Element Table	Overall Length	Weight
460	2-1000	1-100	EIA Flg	Single	5/10/25	3/8 A	7 1/32" (179 mm)	7 lbs (3 kg)
4610-200	2-1000	1-100	EIA Flg	Double	5/10/25	3/8 A	7 1/32" (179 mm)	7 1/4 lbs (3.1 kg)
4805	2-1000	1-100	Unflg	Single	5/10/25	3/8 A	6 1/2" (165 mm)	4 lbs (2 kg)
4802-200	2-1000	1-100	Unflg	Double	5/10/25	3/8 A	6 1/2" (165 mm)	4 1/4 lbs (2.1 kg)
4600-037	50-250	1 1/2-30	EIA Flg	Single	15/30/60	3/8 B	7 1/32" (179 mm)	7 lbs (3 kg)
4610-300	50-250	1 1/2-30	EIA Flg	Double	15/30/60	3/8 B	7 1/32" (179 mm)	7 1/4 lbs (3.1 kg)
4805-037	50-250	1 1/2-30	Unflg	Single	15/30/60	3/8 B	6 1/2" (165 mm)	4 lbs (2 kg)
4802-300	50-250	1 1/2-30	Unflg	Double	15/30/60	3/8 B	6 1/2" (165 mm)	4 1/4 lbs (2 kg)

METER: 4 1/2" meter, shock mounted in aluminum carrying case with 10' (3m) shielded meter cable(s). Dimensions: (WxHxD) 5 5/8" x 6 1/2" x 3 3/8" (141 x 165 x 85).

Single Socket: straight connection

Double Socket: Front panel Forward/Reflected power switch and two shielded cables

TABLE 3 1/8 A
STANDARD ELEMENTS (CATALOG NUMBERS)*

Power Range	Frequency Bands (MHz)					
	2-30	25-60	50-125	100-250	200-500	400-1000
1000 watts		1000A3	1000B3	1000C3	1000D3	1000E3
2500 watts		2500A3	2500B3	2500C3	2500D3	2500E3
5000 watts	5000H3	5000A3	5000B3	5000C3	5000D3	5000E3
10kW	10KH3	10KA3	10KB3	10KC3	10KD3	10KE3
25kW	25KH3	25KA3	25KB3	25KC3	25KD3	25KE3
50kW	50KH3					
100kW	100KH3					

*When ordering, specify catalog number and line section model number.

TABLE 3 1/8 B
STANDARD ELEMENTS
(CATALOG NUMBERS)*

Power Range	Frequency Bands (MHz)	
	50-125	100-250
1500 watts	1500B3	1500C3
3000 watts	3000B3	3000C3
6000 watts	6000B3	6000C3
15kW	15KB3	15KC3
30 kW	30KB3	30KC3

*When ordering, specify catalog number and line section model number.